TWIN BALL DOUBLE BLOCK AND BLEED FLOATING BALL VALVES

HIGH-PERFORMANCE VALVES ENGINEERED FOR THE OIL & GAS, CHEMICAL, PETROCHEMICAL, WATER, AND ENERGY INDUSTRIES



PRODUCT INFORMATION

Negri Fratelli Twin Ball Double Block and Bleed floating ball valves are designed to ensure **maximum safety, reliability and ease of maintenance**, even in critical or high-pressure installations. The twin ball design provides complete shut-off in both directions and allows venting of the internal cavity.

These valves are used in a wide range of applications, including **pipelines, refineries, large power plants, industrial water treatment systems and process lines** where operational continuity and safety are essential.

KEY FEATURES

- **Bolted or fully welded body**
- **Full or reduced bore** options
- **Double Block and Bleed function:** twin ball design with two independent isolation points and cavity venting (through a bleed valve or plug), to drain the fluid trapped between the balls
- **Bi-directional sealing**
- **Solid ball** with a cylindrical bore and no internal cavities
- **Anti-ejection stem** with **antistatic device**
- **Multiple actuation options:** manual lever or gearbox (with handwheel or 90° deviation), or actuator-operated
- **Testing:** hydrostatic and pneumatic tests to API 6D. Other testing upon request

OPTIONAL FEATURES

- **Firesafe certified design:** API 607 and ISO 10497 compliant
- **Versions for cryogenic service**
- **Locking devices**

TECHNICAL SPECIFICATIONS

Design standards	API 6D, ASME B16.34, ASME VIII DIV. 1 / 2, NACE MR0175, EN ISO 14313, EN ISO 17292
Pressure rating	ASME 150 to ASME 2500, PN 6 to PN 420
Temperature range	–10°C to +70°C (other ranges on request)
Size range	up to DN 250 (10”)
End connections:	flanged, butt-welding, hub

MATERIALS

Body and closures	in carbon and stainless steel, obtained from forging or bar stock
Ball	ASTM A479 S41000, ASTM A182 F6a Cl. 2, ASTM A350 Gr. LF2, ASTM A479
Seats	PTFE, RPTFE, Devlon, Peek, PCTFE (other materials on request)
Seals	FKM, HNBR, FFKM, EPDM, graphite, lip seals (other materials and solutions available on request)

CERTIFICATIONS

Design & Construction	API 6D
Firesafe	API 607, EN ISO 10497
Pressure Equipment Directive (PED)	2014/68/EU
ATEX certification	2014/34/EU

Headquarters:
Negri Fratelli Srl
Via dei Martiri, 14
28075 Grignasco (NO) - Italy

Production plant:
Negri Fratelli Srl
Viale Europa, 11
28010 Cavallirio (NO) - Italy

Phone no. +39 0163 417117
Information: info@nfg.it